AGITATORE PER MICROTITER 715

Agitatore a vibrazione rotatoria (eccentricità 3,7 mm) predisposto per contenere fino a 4 piastre Microtiter fissate con molla. Possibilità di alloggiare, a richiesta, 8 piastre. Regolazione elettronica della velocità. Funzionamento in continuo o prefissato mediante timer fino a 60 min. Costruzione esterna in acciaio con verniciatura in polvere. Velocità 300/1500 giri/min.

- Alimentazione elettrica 230 V – 50 Hz . Assorbimento 30 W.
- Dimensioni piano di lavoro mm. 295 x 200.
- Dimensioni d'ingombro mm. 300 x 270 x 200h – Peso Kg. 9.

MICROTITER STIRRER 715

Vibration rotating stirrer (eccentricity 3,7 mm) for holding up to 4 Microtiter plates (fixed by springs). By request 8 plates. Electronic speed regulation. Continuous or predetermined operation by timer up to 60 minutes. Outer casing in powdered painted steel. Speed 300-1500 RPM.
Power supply: 230 V – 50 Hz – 30 W.
Working surface dimensions: 295 x 200 mm.
Overall dimensions: mm. 300 x 270 x 200ht – Weigth: 9 Kg.

AGITATORE PER MICROTITER CON CUPOLA TERMOSTATICA 715/CT

Agitatore a vibrazione rotatoria (eccentricità 3,7 mm) predisposto per contenere fino a 4 piastre Microtiter fissate con molla. Regolazione elettronica della velocità. Funzionamento in continuo o prefissato mediante timer fino a 60 minuti.

- Possibilità di variazione della temperatura di lavoro da ambiente a 50°C regolabili tramite il termoregolatore/visualizzatore digitale.
- Temperatura max.di lavoro all'interno della cupola 50°C Risoluzione +/- 1°C, precisione +/- 0,5°C.
- Cupola termostatica con elettroventola per circolazione aria.
- Dispositivo di arresto agitatore all'apertura della cupola
- Costruzione esterna in acciaio con verniciatura in polvere, cupola in resina acrilica.
- Alimentazione elettrica 230V – 50Hz. Assorbimento 300 W.
- Dimensioni piano di lavoro mm. 270 x 195 x 50 mm h
- Dimensioni d'ingombro mm. 300 x 450 x 240h – Peso Kg. 14.

MICROTITER STIRRER WITH THERMOSTATIC CUPOLA 715/CT

Vibration rotating stirrer (eccentricity 3,7 mm) for holding up to 4 Microtiter plates (fixed by springs). Electronic speed adjustment. Continuous or preset operation by timer up to 60 minutes. Thermostatic acrylic resin cupola with electrical fan for air circulation. Temperature rate set to 50°C with digital reading. Resolution +/- 1°C, precision +/- 0,5°C. Temperature control adjustable within a range from room temperature up to 50°C with digital thermoregulator. Max working temperature inside the cupola 50°C. Safety locking device stopping the stirrer at cupola opening. Outer casing in powdered painted steel. Power supply: 230 V – 50 Hz – 300 W.

- *Working surface dimensions: 270 x 195 x 50 mm h.*
- *Overall dimensions: mm. 300 x 450 x 240ht – Weigth: 14 Kg.*

FRANCESCHI
S.A.S.
ATTREZZATURE SCIENTIFICHE PER LABORATORIO
PRODOTTI CHIMICI PURI PER ANALISI
56010 GHEZZANO (PI) - Via Carducci, 31 - Cod. Fisc. e Partita I.V.A. 01227260500
Tel. 050 879 980 - Fax 050 879 984 - e-mail: franceschimica@tiscalinet.it